

WOODWORKING DUST COLLECTION HOSE



A Air **F** Fume **D** Dust **M** Material



PRODUCT	SIZE	LENGTH	TEMP RANGE	DESCRIPTION	Abrasion Resistant
Flexadux® PU					
• Flx-Thane® LD <i>light weight</i>	2" to 18"	25'	-65° to 225°	<i>Light weight polyurethane hose reinforced with a bronze coated spring steel wire helix: Great compressibility & flexibility; Ideal for dust collection, fume removal and oil mist collection; Wall thickness .020"; Available in metric sizes</i>	A F D
• Flx-Thane® MD <i>medium weight</i>	2" to 24"	25', 50'	-65° to 225°	<i>Medium weight polyurethane hose reinforced with a bronze coated spring steel wire helix: Great flexibility and excellent tear strength; Withstands puncture and abrasion; Can handle more severe service applications than standard neoprene hose; Wall thickness .030"; Available in metric sizes</i>	M
• Flx-Thane® HD <i>heavy weight</i>	2" to 24"	25'	-65° to 225°	<i>Heavy weight polyurethane hose reinforced with a coated spring steel wire helix: Great abrasion resistance & higher tear strength; Ideal for severe service applications, wood chips and material handling; Wall thickness .045"; Available in metric sizes</i>	M



PRODUCT	SIZE	LENGTH	TEMP RANGE	DESCRIPTION	All-Purpose
Flexadux® TR					
• T-7	2" to 24"	25', 50'	-60° to 275°	<i>Medium weight thermoplastic rubber hose reinforced with a spring steel wire helix: Traditional all-purpose dust collection and ventilation hose; Excellent chemical, moisture and UV resistance; Wall thickness .030"; Available in metric sizes</i>	D M



PRODUCT	SIZE	LENGTH	TEMP RANGE	DESCRIPTION	Economical
Flexadux® PV					
• R-4	2" to 12"	10', 25', 50'	20° to 160°	<i>Medium weight PVC hose reinforced with a spring steel wire helix: Highly compressible; Ideal for dust collection in woodworking applications; The clear hose allows user to see blockages; Value packaging available reducing the box size, warehouse space & shipping costs; Wall thickness .028"</i>	D M

1510 Armstrong Road, P.O. Box 4275 Warsaw, IN 46581-4275
 toll free: 800-343-0428 / tel: 574-267-7909 / toll free fax: 800-382-8464 / fax: 574-269-7491
 sales@flexaust.com

www.flexaust.com

DISTRIBUTED BY:

