

SPECIFICATION DATA:

	IG-55/85 COS(5)	IG-90/65 COS(12)	IG-90/75 COS(12)	IG-90/85 COS(8)	IG-90/85 CBS(12)	IG-120/85 COS(12)	IG-120/85 COS(16)
Reinforcement	Multifilament	Staple	Staple	Staple	Staple	Staple	Staple
Warp	Polyester	Polyester	Polyester	Polyester	Polyester	Polyester	Polyester
Weft	Multifilament	Staple	Staple	Staple	Staple	Staple	Staple
	Polyester	Polyester	Polyester	Polyester	Polyester	Polyester	Polyester
Tension Rating (PIW)	55	90	90	90	90	120	120
1% Elongation (PIW)	90	85	85	85	85	170	170
Maximum Belt Width	48"	48"	72"	72"	48"	72"	48"
Random Slab Length	300'	80'	300'	300'	300'	500'	300'
Overall Thickness	5/64"	3/16"	3/16"	1/8"	3/16"	3/16"	1/4"
Colors	Clear	Clear	Black	Red	Red	Red	Red
Cover Durometer(Shore A)	85	65	75	85	85	85	85
Top Cover Thickness	3/64"	1/8"	1/8"	1/16"	1/16"	3/32"	3/32"
Bottom Cover Thickness	FS	FS	FS	FS	1/16"	FS	1/16"
Minimum Pulley Diameter	1"	3"	3"	2"	3"	4"	4"
Weight Per Foot (PIW)	.038#	.104#	.104#	.079#	.104#	.094#	.121#
Temperature (Deg.F)							
Minimum	40	0	0	0	0	0	0
Maximum	175	185	185	185	185	185	185
Coefficient of Friction							
Top Cover	.38	.145	1.15	.85	.85	.90	.90
Bottom Cover	.22	.43	.40	.25	.85	.22	.90
Meets FDA	Yes	No	No	Yes	Yes	Yes	Yes
USDA Approved	Yes	No	No	No	No	No	No
Mechanical Fasteners							
Flexco	#62	#125	#125	#62	#125	#125	#187
Gator	#1AD	#3G	#3G	#2	#3G	#3G	#3G
Clipper	#25LP	#2	#2	#2	#2	#2	#4