Omni Metalcraft corp.

□ AC Speed Controller □ DC Speed Controller

☐ Mechanical Variable Speed Adjustment

Approval Drawing Required: ☐ Yes ☐ No

Horsepower: ____

CHAIN CONVEYOR QUOTATIO	N WORKSHE	EI						
Company	Date							
Contact								
Phone No.:								
Omni Sales Contact:				e #:				
Quantity:								
duality								
Product Specs:		Plant Volt	tage:					
Max:			V Single	Phase	4	60V Three P	hase	
Width (inches): Length (inches):			V Single		 2	208V Three Pl	hase	
Height (inches):Weight (lbs):		220 ′	V Three I	Phase	□ 5	75V Three P	hase	
Min:								
Width (inches): Length (inches):		Application	on Info	rmation:	i i			
Height (inches): Weight (lbs):			Enters B	•				
Description:			nveyed O	n	☐ F	ork Truck		
Max. Qty.: Total Live Load:						Other		
Temperature			Exits By:					
Environment:			nveyed of	f		ork Truck		
Product:		Rob				Other		
		Interfacir	-			10 Town Tile		
Conveyor Construction:		Stac				Lift, Turn, Tilt Strapper		
☐ Welded		- mappo				□ Strapper		
☐ Painted ☐ Epoxy Painted ☐ Stainle	ess Steel	- Ou.,	eı					
Powder Coated Color RAL:		Notes:						
		140100						
Conveyor Specifications:								
Chain Speed:								
Top of Chain:								
Length (approx.):								
# of Strands:								
Strand CC:								
OA Strand CC:								
Roll Centers at Strands:								
Chain Size:		Chart E	Based on	1.0		yors @ 30 FP	M Fixed	
☐ C50 ☐ C60 ☐ C80 ☐ C100 ☐ I	DC100			S	Speed			
		Max	Chain	Chain	Min. To	p Min.	Max Live	
Other:		Unit Load	Size	Track	of Chai		Load	
Also Available:		500	C50	UHMW	10"	8"	500	
Power Twist Belt and C50 & C80 pade	ded chain.				-	_		
Tomor Timor Zon and Late I. I. I.	Jou ona	1500	C60	UHMW	14"	9"	6,800	
Chain Track:		2000	C60	UHMW	14"	14"	6,800	
		3000	C80	UHMW	15"	14"	10,000	
☐ UHMW ☐ Steel ☐ Other:		4000	C80	Steel	16"	16"	9,600	
		6000	C100	Stool	18"	36"	9.600	