

## HYDRAULIC TILTER QUOTATION WORKSHEET

Company \_\_\_\_\_ Date \_\_\_\_\_  
Contact \_\_\_\_\_ Quote Due \_\_\_\_\_ Desired Delivery \_\_\_\_\_  
Phone No.: \_\_\_\_\_ Contact Email: \_\_\_\_\_ State \_\_\_\_\_  
Omni Sales Contact: \_\_\_\_\_ Quote #: \_\_\_\_\_  
Quantity: \_\_\_\_\_

## APPLICATION INFORMATION

How is tilter to be used? \_\_\_\_\_  
\_\_\_\_\_

Equipment mounted to the tilter: \_\_\_\_\_

**Product Description:** \_\_\_\_\_

Size: \_\_\_\_\_ W x \_\_\_\_\_ L x \_\_\_\_\_ H, WT = \_\_\_\_\_ LBS.

### Tilter Information:

Capacity: \_\_\_\_\_ Platform Length: \_\_\_\_\_ Platform Width: \_\_\_\_\_

**Height Info.:** Lowered \_\_\_\_\_  
Degree of Tilt \_\_\_\_\_ (0° - 60°)

**Cycle Info.:** Jogs/Cycle \_\_\_\_\_  
Cycles/Hour \_\_\_\_\_

### Power Unit:

- External
- Internal
- None

### Plant Voltage:

- 110V Single Phase
- 220V Single Phase
- 220V Three Phase
- 440V Three Phase
- 208V Single Phase
- 575V Three Phase

### Controls:

- Foot Pedal
- Hand Held Pendant
- No Controller
- Less All Controls

### How is tilt loaded?

- End
- Side

### How is tilt off loaded?

- End
- Side

### Options:

- Skirting
- Stainless

### Lip on Hinged End:

(Standard is 8 in.)

- Yes
- No
- Other \_\_\_\_\_

**Other:** \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Approval Drawing Required:  Yes  No