



PRODUCT BULLETIN

NOVITANE® • SHEETING • CONVEYOR BELTING • CUSTOM PRODUCTS

**NOVITANE®
SHEET LINING
IMPACT RESISTANCE GUIDE**

NOVITANE sheet lining material has been specifically formulated to provide superior resistance to impact, tearing, cutting and abrasion in service applications commonly found in the metallic and non-metallic mining, cement, sand and gravel industries.

Since the ultimate service life of **NOVITANE** sheet lining is dependent upon such factors as material size and free fall drop distance, the following table can be used as a **guide** in determining the thickness of **NOVITANE** lining to use.

<u>MATERIAL SIZE</u>		<u>NOVITANE THICKNESS GUIDE</u>									
	Drop (ft.)	0-2'	3'	4'	5'	6'	8'	10'	12'	15'	
1/8" - 1/4"		1/4"	3/8"	3/8"	1/2"	1/2"	1/2"	1"	1 1/4"	1 1/2"	
3/8" - 1/2"		1/4"	3/8"	1/2"	1/2"	3/4"	3/4"	1 1/4"	1 1/2"	1 3/4"	
3/4" - 1"		1/2"	1/2"	3/4"	3/4"	1"	1 1/2"	1 3/4"	2"	2"	
2"		1/2"	3/4"	3/4"	1 1/4"	1 1/2"	1 3/4"	2"	2"		
4"		3/4"	1"	1 1/2"	1 3/4"	2"	2"				
6"		1"	1 1/2"	1 3/4"	2"	2"					
8"		2"	2"	2"							
10"		2"	2"								



7/27/99