

## WOODWORKING DUST COLLECTION HOSE

### Dust Collection Hose

#### T-7

**D M**

Size: 1.5" to 24"  
Length: 25', 50' (up to 12")  
Temp Range: -60° to 275°



**GOOD**

#### Flx-Thane® LD

**A F D**

Size: 2" to 18"  
Length: 25'  
Temp Range: -65° to 200°



**BETTER**

#### Flx-Thane® MD

**M**

Size: 2" to 18"  
Length: 25', 50' (up to 12")  
Temp Range: -65° to 200°



**BEST**

Medium weight thermoplastic rubber hose reinforced with a spring steel wire helix: Traditional all-purpose dust collection and ventilation hose.

Light weight polyurethane hose reinforced with a bronze coated spring steel wire helix.

Medium weight polyurethane hose reinforced with a bronze coated spring steel wire helix.

### Static Control Hose

#### Flx-Thane® LD-SD

**A F D**

Size: 2" to 12"  
Length: 25'  
Temp Range: -65° to 200°



Light weight clear static dissipative polyurethane hose reinforced with a bronze coated spring steel wire helix. Surface resistivity level of:  $10^8$ - $10^{10}$  Ohms/Square.

#### Flx-Thane® SD

**M**

Size: 2" to 12"  
Length: 25', 50' (up to 12")  
Temp Range: -65° to 200°



Medium weight static dissipative polyurethane hose reinforced with a bronze coated spring steel wire helix. Surface resistivity level of:  $10^8$ - $10^{10}$  Ohms/Square.

#### FlexStat®

**F D M**

Size: 1" to 8"  
Length: 25', 50'  
Temp Range: -40° to 200°



Specially formulated static dissipative polyurethane hose reinforced with a rigid ABS helix and an embedded copper grounding wire. Surface resistivity level of:  $10^8$ - $10^{10}$  Ohms/Square.

### CNC Vacuum Hose & Accessories

#### Flex-Tube® PU 60 HF

**M**

Size: 2" to 8"  
Length: 25', 50'  
Temp Range: -40° to 200°



Highly flexible very heavy weight thermoplastic polyether polyurethane hose with a rigid external ABS helix.

#### Flex-Tube® Bridge Clamps

- Specially designed stainless steel band and welded stainless steel bridge with stainless steel screw
- Fits over helix creating a leak proof seal
- Available in sizes 4" to 12"



#### Flex-Tube® Swivel Connector

- Designed to make it easier to maneuver longer (connected) lengths of hose
- Available in sizes 2", 2.5", 3", 4", 6"
- Made with high strength polyurethane to withstand application abuse
- Secure with Flex-Tube bridge clamps or T-bolts (2", 2.5" & 3")



### Shop Vacuum Clean-Up Kits

#### Industrial MRO General Pick-Up Kit

Designed to fit all standard Wet/Dry Vacuums

- 1.5" x 15' StatPath® Plus Hose with Swivel Cuff and Inlet Adapter
- 4" Utility Tool
- 11" Crevice Tool



#### Commercial MRO General Pick-Up Kit

Designed to fit all standard Wet/Dry Vacuums

- 1.5" x 12' Flx Plus Hose with Swivel Cuff and Inlet Adapter
- 4" Utility Tool
- 11" Crevice Tool



#### Commercial MRO General Pick-Up Kit POP Display

10 kits, each kit includes:

- 1.5" x 12' Flx Plus Hose with Swivel Cuff and Inlet Adapter
- 4" Utility Tool
- 11" Crevice Tool



California Residents:  
**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).