

# DEFENDER

Highly absorbent sonic bonded mat for oily spills and overspray



## Features and Benefits

- Abrasion-resistant top layer gives pads and rolls strength for everyday cleanup jobs
- Perfect for medium-duty industrial, maintenance and general applications
- Quickly absorbs leaks, spills and overspray to keep floors dry
- Perforations allow you to tear pads and rolls into different sizes based on your application
- Oil selective — repels water but absorbs oil and all oil-based fluids
- Pads perforated at 7.5" up the center
- Rolls perforated every 7.5" vertically and cross-perforated at 17" horizontally

## DEFENDER™ Mat

### White Oil-Only Pads

Item #	Description	Size	Units/Pkg	Absorbs/Pkg
WPB100H	HeavyWeight Pads	15" x 19"	100	29.1 gal.
WPB50H	HeavyWeight Pads	15" x 19"	50	14.6 gal.
WPKB50H	HeavyWeight King Pads	30" x 30"	50	45.3 gal.
WPB100M	MediumWeight Pads	15" x 19"	100	24.7 gal.
WPB50M	MediumWeight Pads	15" x 19"	50	12.4 gal.
WPB200S	LightWeight Pads	15" x 19"	200	31.1 gal.
WPB100S	LightWeight Pads	15" x 19"	100	15.6 gal.


### White Oil-Only Rolls

Item #	Description	Size	Units/Pkg	Absorbs/Pkg
WRB150H	HeavyWeight Roll	30" x 150'	1	55.2 gal.
WRSB150H	HeavyWeight Split Rolls	15" x 150'	2	55.2 gal.
WRB150M	MediumWeight Roll	30" x 150'	1	46.1 gal.
WRSB150M	MediumWeight Split Rolls	15" x 150'	2	46.1 gal.
WRB300S	LightWeight Roll	30" x 300'	1	59.1 gal.



### DEFENDER Mat Construction

One layer of spunbond fabric is ultrasonically bonded to a single layer of meltblown sorbent.



**HYC**

Helps you comply with 29 CFR 1910.22(a)(2), 29 CFR 1910.107(b)(3), 29 CFR 1910.107(g)(2), 29 CFR 1910.120(j)(1), 29 CFR 1910.1450(e), and 49 CFR 173.12 (b)(2)(iv). See page 99 for details.