

PROTECTOR

Tough multi-laminate mat stands up to punishing applications





PROTECTOR Mat Construction Meltblown sorbent is ultrasonically bonded between two layers of lint-free spunbond fabric. Spunbond Spunbond



Helps you comply with 29 CFR 1910.22(a)(2), 29 CFR 1910.120(j)(1), 29 CFR 1910.1450(e) and 49 CFR 173.12 (b)(2) (iv). See page 99 for details.

Features and Benefits

- Abrasion-resistant outer layers of spunbond material add durability for long life
- Low-linting mat is a great choice for lining tool benches, wiping down machinery or cleaning oily tools and parts
- Perfect for industrial applications in demanding environments where durability is most important
- Perforations allow you to tear pads and rolls into different sizes based on your application
- Pads perforated at 7.5" up the center
- Rolls perforated every 7.5" vertically and cross-perforated at 17" horizontally

PROTECTOR™ Mat

Gray Universal Pads (for oils, coolants, solvents & water)						
Item #	Description	Size	Units/Pkg	Absorbs/Pkg		
GPL100H	HeavyWeight Pads	15" x 19"	100	28.9 gal.		
GPL100M	MediumWeight Pads	15" x 19"	100	23.4 gal.		

Gray Universal Rolls (for oils, coolants, solvents & water)						
Item #	Description	Size	Units/Pkg	Absorbs/Pkg		
GRL150H	HeavyWeight Roll	30" x 150'	1	54.9 gal.		
GRSL150H	HeavyWeight Split Rolls	15" x 150'	2	54.9 gal.		
GRL150M	MediumWeight Roll	30" x 150'	1	44.4 gal.		
GRSL150M	MediumWeight Split Rolls	15" x 150'	2	44.4 gal.		